

JASCO®

Premium Quality Since 1952



PRE-PAINT PREPARATION

LIQUID SANDER

BEFORE YOU
PAINT OR REFINISH!

1 QUART

946 mL

PREPS & DEGLOSSES – NO SANDING NEEDED

WARNING! HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. Read other cautions on side panel.

JASCO Liquid Sander & Paint Etch is a ready-to-use liquid deglosser that saves time and labor. This product is formulated for use by the professional and homeowner who desires to save time and effort while achieving a high quality paint application on previously painted and glossy surfaces. Liquid Sander works in one easy wipe-on application WITHOUT MIXING, WASHING OR SANDING to degloss old coated surfaces. This allows NEW paint, enamel, varnish, urethane, lacquer, shellac, stain or wallpaper to bond. Its etching - abrasive action forms a perfect base for new paint or coating. Low odor and non-flammability makes it ideal for use in kitchen or bathroom as well as other interior/exterior applications. Semi transparent stains do not provide coverage over old paint.

USES:

• DEGLOSSES • ETCHES • REMOVES DIRT, WAX, INK, TAR • FOR PAINTED & VARNISHED SURFACES

FEATURES:

• EASY TO USE • ELIMINATES SANDING – SAVES TIME • IMPROVES PAINT BOND • NON-FLAMMABLE • LOW ODOR

Unfinished Wood: Removes dirt, pencil, crayon, ink, dust scuff, finger and heel marks without raising grain of wood.

Panels & Floors: Removes wax, tar, dirt, dust, shoe and furniture marks. Always wipe in direction of grain.

Always test first on an inconspicuous surface for compatibility and on nearby surfaces that are not to be refinished, as it will degloss most surfaces.

DIRECTIONS

APPLY: This product is premixed. Shake well before use. Wipe Liquid Sander on with a coarse cloth, or brush (or steel wool on heavily soiled, waxed or rough surfaces).

REMOVE: Let stand for a few minutes, then wipe off dust, dirt, or wax with a clean cloth. Heavily soiled or waxed surfaces may need additional applications to remove all residue.

WAIT: Let all surfaces completely dry. (Typically, dry to the touch in 2 hours)

FINISH: Refinish now or next week before surface becomes dusty or dirty again. If it does, rewipe with Liquid Sander and refinish. (Apply antiquing promptly after etching.)

CLEANUP: Clean up tools and any spills with water.

WARNING: Contains Dibasic Esters, 2-Butoxyethanol and Ethoxylated Octyl Phenol. Use only in a well-ventilated area. Avoid breathing vapors or spray mists. Avoid contact with eyes, skin and clothing. Wear safety glasses or goggles and rubber gloves when handling. Do not take internally.

FIRST AID: If swallowed, call a poison center or physician immediately. Do not induce vomiting unless directed to do so by medical personnel. In case of eye contact, immediately flush eyes with water for 15 minutes. Get medical attention if irritation persists. If on skin, wash thoroughly with water for 15 minutes. If inhaled, remove to fresh air. If difficulty with breathing continues, seek medical attention.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Item #0402
PN 400-201026
MN 12157
1207



Homax Products, Inc.
P.O. Box 5643 • Bellingham, WA 98227
(800) 729-9029 • www.homaxproducts.com

